

LED slim sensor projector

Barcode: 8433325213831



Specification

| | |
|-------------|-----------------------|
| Dimension | L176.8*W179.6*H54.1mm |
| Wire length | 250mm |
| Wire | 3x1.0mm ² |
| Technology | LED |

Technical parameters

| | |
|-----------------------------------|-------------|
| Voltage | 220-240V~ |
| Luminous flux | 2450lm |
| EEL | F |
| Current | 140mA |
| CRI | Ra≥80 |
| Beam angle | 90° |
| Hg% | Zero |
| Power | 30W |
| Incandescent Lamp Power | 30W |
| Incandescent Lamp Power | 30W |
| Frequency | 50/60Hz |
| Color temperature | 6500K |
| Power consumption per 1,000 hours | 30kWh/1000h |

Application environment

| | |
|-------------|--------------------|
| Environment | Indoor and outdoor |
|-------------|--------------------|

| | |
|---------------------|--------------|
| Working Temperature | -10°C ~ 50°C |
| Protection | IP65 |

Life span

| | |
|---------------------|--------------|
| Life span | ≥100000h |
| Switching frequency | ≥100000times |

Material

| | |
|----------------|----------|
| Main Materials | Aluminum |
|----------------|----------|

Certification

| | |
|---------------|---|
| Certification |   |
|---------------|---|

Package

| | |
|-------------------|--------------|
| Package | pc/color box |
| Outer Package | pcs/ctn |
| Unit package qty | One |
| Outer package qty | Twenty |

Certification Download

Instruction
manual

[Download](#)