

E6 LED Ultra-thin Flush-mounted Square Downlight 6W Yellow Light

Barcode: 8433325292119



Specification

| | |
|-------------|-----------------|
| Dimension | L115*W115*H32mm |
| Cutout size | Φ100-110mm |
| Technology | LED |

Technical parameters

| | |
|-----------------------------------|------------|
| Voltage | 220-240V ~ |
| Luminous flux | 320lm |
| EEL | A |
| Current | 50mA |
| CRI | Ra≥80 |
| Beam angle | 160° |
| PF | > 0.5 |
| Hg% | < 0.1% |
| Power | 6W |
| Incandescent Lamp Power | 30W |
| Frequency | 50/60Hz |
| Color temperature | 3000K |
| Power consumption per 1,000 hours | 6kwh/1000h |

Application environment

| | |
|-------------|--------|
| Environment | Indoor |
|-------------|--------|

| | |
|---------------------|---------------|
| Working Temperature | -20°C ~ 40°C |
| Installation method | Flush-mounted |

Life span

| | |
|---------------------|------------|
| Life span | 20000h |
| Switching frequency | 12500times |

Material

| | |
|----------------|------------------|
| Main Materials | plastic&aluminum |
|----------------|------------------|

Certification

| | |
|---------------|---|
| Certification |   |
|---------------|---|

Package

| | |
|-------------------|--------------|
| Package | pc/color box |
| Outer Package | pcs/ctn |
| Unit package qty | One |
| Outer package qty | Twenty |

Certification Download

Instruction
manual

Download