

LED Sensor Slim Flood Light Die Casting

Barcode: 8433325198428



Specification

| | |
|-------------|-----------------|
| Dimension | L147*W182*H56mm |
| Wire length | 225mm |
| Technology | LED |

Technical parameters

| | |
|-----------------------------------|-------------|
| Voltage | 220-240V ~ |
| Luminous flux | 2700lm |
| EEL | A+ |
| Current | 134mA |
| CRI | Ra≥80 |
| Beam angle | 120° |
| PF | > 0.9 |
| Hg% | Zero |
| Power | 30W |
| Frequency | 50/60Hz |
| Color temperature | 4000K |
| Power consumption per 1,000 hours | 30kwh/1000h |

Application environment

| | |
|---------------------|--------------|
| Environment | Outdoor |
| Working Temperature | -20°C ~ 40°C |
| Protection | IP65 |

Life span

| | |
|---------------------|------------|
| Life span | 25000h |
| Switching frequency | 20000times |

Material

| | |
|----------------|----------------|
| Main Materials | Glass&Aluminum |
|----------------|----------------|

Certification

| | |
|---------------|---|
| Certification |   |
|---------------|---|

Package

| | |
|-------------------|--------------|
| Package | pc/color box |
| Outer Package | pcs/ctn |
| Unit package qty | One |
| Outer package qty | Twenty |

Certification Download

Instruction
manual

Download