

LED ceiling light

Barcode: 8433325192716



Specification

| | |
|------------|------------|
| Dimension | D300*H50mm |
| Technology | LED |

Technical parameters

| | |
|-----------------------------------|-------------|
| Voltage | 50/60Hz |
| Luminous flux | 2100lm |
| EEL | F |
| Current | 170mA |
| CRI | Ra≥80 |
| Beam angle | 120° |
| Hg% | Zero |
| Power | 20W |
| Incandescent Lamp Power | 131W |
| Frequency | 50Hz/60Hz |
| Color temperature | 4000K |
| Power consumption per 1,000 hours | 20kwh/1000h |

Application environment

| | |
|---------------------|------------|
| Environment | Indoor |
| Working Temperature | 0°C ~ 30°C |

Life span

| | |
|-----------|--------|
| Life span | 15000h |
|-----------|--------|

Material

| | |
|----------------|----------------|
| Shell material | Plastic |
| Main Materials | Plastic & Iron |

Certification

| | |
|---------------|---|
| Certification |   |
|---------------|---|

Package

| | |
|-------------------|--------------|
| Package | pc/color box |
| Outer Package | pcs/ctn |
| Unit package qty | One |
| Outer package qty | Six |

Certification Download

Instruction
manual

[Download](#)